

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR U.S. LETTERS PATENT

Title:

COMPLEMENTARY BIT PCRAM SENSE AMPLIFIER
AND METHOD OF OPERATION

Inventors:

R.J. Baker
Glen Hush

Thomas J. D'Amico
DICKSTEIN SHAPIRO MORIN &
OSHINSKY LLP
2101 L Street NW
Washington, DC 20037-1526
(202) 828-2232

TITLE OF INVENTION
COMPLEMENTARY BIT PCRAM SENSE AMPLIFIER
AND METHOD OF OPERATION

FIELD OF THE INVENTION

[0001] The invention relates to a method and apparatus for sensing the resistance of a Programmable Conductor Random Access Memory (PCRAM) element.

BACKGROUND OF THE INVENTION

[0002] PCRAM devices store binary data as two different resistance values, one higher than the other. The resistance value represents a particular binary value of logic "0" or logic "1". When sensing the resistance value of a PCRAM device, it is common to compare the resistance of a memory cell undergoing a read operation with resistance of a reference cell to determine the resistance value of the cell being read and thus its logic state. Such an approach is disclosed in U.S. Patent No. 5,883,827. However, this approach has some limitations.

[0003] If the reference cell is defective and a column of memory cells within an array uses a same defective reference cell, the entire column of memory cells will have erroneous resistance readings. In addition, specialized circuitry is required to write a resistance value into the reference cell, and a sense amplifier circuit for such an arrangement tends to be complex and large.

[0004] Typically, sensing schemes for PCRAM devices also tend to have a unique architecture which is different from that normally employed in typical DRAM circuits. Although PCRAM's differ from DRAM's in that they store

binary values in resistive memory elements rather than as charges on capacitors, and although PCRAM's are non-volatile, where the capacitor structures employed in DRAM's are volatile, nevertheless it would be desirable if the read and write circuits for both devices were as similar as possible so that existing DRAM memory device architectures could be easily adapted to read and write PCRAM devices.

BRIEF SUMMARY OF THE INVENTION

[0005] The present invention provides a PCRAM memory device and its method of operation which utilizes a read architecture similar to that employed in some DRAM memory devices. A pair of complementary PCRAM memory cells comprising first and second programmable conductor memory elements are employed, each connected to respective access transistors. During a write operation, the first and second memory elements are written with complementary binary values, that is: if the first memory element is written to a high resistance state, then the second memory element is written to a low resistance state; whereas if the first memory element is written to a low resistance state, the second memory element is written to a higher resistance state.

[0006] During a read operation of, for example, the first memory element, a sense amplifier is connected so that its respective inputs are coupled to receive respective precharge voltages which discharge through the first and second memory elements. A sense amplifier reads the discharging voltages through the two memory elements to determine which is the larger voltage, thus determining

the resistance (high or low) and logic state (high or low) of the memory cell being read.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] These and other features and advantages of the invention will become more apparent from the following detailed description of exemplary embodiments of the invention which are provided in connection with the accompanying drawings in which:

[0008] Figure 1 shows an exemplary PCRAM device;

[0009] Figure 2 is a schematic diagram depicting one aspect of the invention;

[00010] Figure 3 is a schematic diagram depicting an additional aspect of the invention;

[00011] Figure 4 is a schematic diagram depicting an additional aspect of the invention;

[00012] Figure 5 shows the discharge rate characteristics of capacitors employed in the invention;

[00013] Figure 6 shows the invention utilized in a computer system.

DETAILED DESCRIPTION OF THE INVENTION

[00014] The present invention employs a sense amplifier architecture which is somewhat similar to that employed in some conventional DRAM devices to sense

the resistance states of PCRAM memory cells. In the invention, a binary value is stored as a resistance value in a first PCRAM cell while its complement resistance value is stored in a second PCRAM cell. During readout of the first PCRAM cell, both PCRAM cells are used to discharge a precharge voltage into respective inputs of a sense amplifier which reads the discharge voltages to determine the resistance and thus the binary value stored in the first PCRAM cell undergoing a read operation.

[00015] Figure 1 illustrates an exemplary cell arrangement provided within a portion of a PCRAM memory device constructed in accordance with the invention. A PCRAM memory element 102 is illustrated which has a chalcogenite glass body and lower 103 and upper 104 conductors. As is well known, a programmable conductor memory element has two stable resistance states: one high resistance and one low resistance. Normally, when at rest the memory has a high resistance state, but it can be programmed to a low resistance state by suitably applying bias voltages to the conductors 103 and 104. Typically, the low resistant state of a PCRAM memory element is characterized by a dendrite growth through the chalcogenite glass body or along the surface of the chalcogenite glass body between the conductors 103 and 104. A high resistant state is present when there is no such dendrite growth. The grown dendrite is relatively non-volatile in that it will remain in place for a relatively long time, e.g. days or weeks, after the bias voltage is removed.

[00016] As further shown in Figure 1, the PCRAM memory element 102 is coupled by a conductive plug 101 to an access transistor 207 which is driven by a word line 105 which forms the gate structure of transistor 207. The access transistor is coupled through conductive plug 101 to one of the conductors 103

of the PCRAM memory element. The other conductor 104 of the PCRAM element is connected by a common cell plate 109 to a bias voltage, which is common to other PCRAM memory elements provided in the memory device.

[00017] Figure 1 illustrates a common PCRAM architecture in which two adjacent memory cells 207, 211 are coupled to a common digit line 118. Thus, Figure 1 also shows another access transistor 211 driven by a word line 107 which is connected through conductive plug 99 to another PCRAM memory element 104, which in turn is also connected also to the common cell plate 109. Access transistor 211 also has one terminal connected to digit line 118.

[00018] Figure 2 shows an electrical schematic arrangement of a memory array employing the cell architecture illustrated in Figure 1. Thus, the top portion of Figure 2 illustrates the transistors 207 and 211 coupled to the respective PCRAM memory elements 102 and 106 with the access transistors 207 and 211 coupling the memory elements 102 and 106 to the digit line 118.

[00019] As also illustrated in Figure 2, a complementary digit line D1* 120 is also provided in the memory array, to which another set of access transistors is connected which are in turn connected to other PCRAM memory elements. To simplify discussion, a single complementary pair of PCRAM cells is illustrated as 300. It includes transistor 207 and associated PCRAM memory element 102, which is coupled to the digit line 118 (D1), and an access transistor 209 and associated PCRAM memory element 124, which are coupled to digit line 120 (D1*).

[00020] During a write operation, a row line 104, which is coupled to transistor 207 and a row line 113 which is coupled to transistor 209 are activated

such that if PCRAM memory element 102 is written to a high resistance state, PCRAM element 124 is written to a low resistance state, and vice versa. In this way, PCRAM memory elements 102 and 124 are accessed together and always store complementary resistance digit values. Thus assuming that PCRAM memory element 102 is the primary element which is being written to and read from, a sense amplifier 210 which is coupled to the digit lines 118 and 120 will read the value of PCRAM memory element 102 by comparing a discharging precharge voltage on digit line 118 to the discharging precharge voltage on digit line 120 during a memory read operation.

[00021] Thus, prior to a memory read, a precharge voltage is applied to complementary digit lines 118 and 120 by a precharge circuit 301. The precharge circuit is activated by a logic circuit on a precharge line which activates transistors 305 to supply a voltage, for example, $V_{cc}/2$, to both digit lines 118 and 120.

[00022] An equilibrate circuit 303 may also be provided which is activated by an equilibrate signal after the precharge circuit is activated to ensure that the voltages on lines 118 and 120 are the same. The voltages on lines 118 and 120 are held by a parasitic capacitance of the lines. After precharge and equilibrate (if present) circuits are activated, a read operation may be conducted on the complimentary cell pair 300. This read operation is illustrated in greater detail in Figure 3, which is a simplification of the sense amplifier 210 input path.

[00023] Parasitic capacitance for the complementary digit lines 118 and 120 are illustrated as C1 and C1*. The respective access transistors 207 and 209 are illustrated as connected to their respective word lines 105 and 113. The

PCRAM memory elements 102 and 124 are also illustrated. As noted, a binary value is stored, for example, in memory PCRAM memory element 102 as a resistance value. It will be either a high resistance value or a low resistance value, and the complementary resistance value will be stored in PCRAM memory element 124.

[00024] During a read operation, the precharge voltage applied to the complementary digit lines 118 and 120 is allowed to discharge through the access transistors 207 and 209 and through the respective resistance values of the PCRAM memory elements 102 and 124. Because the resistance values will be different, one high and one low, the voltages on the digit lines D1 and D1* (118, 120) will begin to diverge during a read operation. Although the voltage initially applied to the complementary digit lines 118 and 120 is a voltage of $V_{cc}/2$, during a read operation this voltage actually is slightly higher by approximately .3mV due to the presence of the parasitic capacitance C1 and C1* on the digit lines 118 and 120, as well as gate-drain capacitance inherent within transistors 207 and 209.

[00025] Figure 5 illustrates the voltages on the complementary digit lines 118 and 120 during a read operation. The activation of the word lines 105 and 113 is illustrated as a pulse signal, and initially the voltage of $V_{cc}/2$ + approximately .3mV which exists on both digit lines D1 and D1* begins to decay. Because one PCRAM memory element, e.g. 102, has a higher resistance than the other, the voltage on the digit line associated with the lower resistance value, e.g. 124, will decay faster than the voltage on the digit line coupled to the higher resistance value, e.g. D1. This is illustrated in Figure 5.

[00026] The divergence of the two voltages on the lines D1 and D1* progressively increases. At a predetermined time after the word lines 105 and 113 are activated, the sense amplifier 210 is activated. The sense amplifier can have an architecture typically employed in a DRAM arrangement which is illustrated in Figure 4. Such a sense amplifier includes an Nsense amplifier latch 302 and a Psense amplifier latch 304. This structure is illustrated in Figure 4.

[00027] Reverting back to Figure 5, the N sense amplifier is fired first at a time t_1 . When the Nsense amplifier fires, the digit line which has the lower voltage, e.g. D1* in the example, is immediately pulled to ground. Thereafter, the Psense amplifier is fired at a time t_2 which drives the higher voltage line, e.g. D1, to Vcc. Accordingly at a time t_2 , the sense amplifier 210 outputs a value of Vcc indicating the high resistant state for the PCRAM memory element 102.

[00028] Although Figure 5 illustrates the signal timing which occurs when PCRAM memory element 102 has a higher resistance than memory element 104, obviously the signal levels are reversed if PCRAM memory element 102 has a low resistance state and PCRAM memory element 124 has a high resistance state. That is, the signal diagrams illustrated in the Figure 5 would have the digit line D1* going towards Vcc and the digit line D1 going towards ground.

[00029] Figure 5 also illustrates another aspect of the invention. As shown, the voltage for row lines 105, 113 increases from near ground level to a positive voltage near Vcc for a read operation. This voltage then returns to near ground level before the sense amplifier is enabled (before t_1). As a result, there is no rewriting of a read PCRAM memory element. If such rewriting of a PCRAM cell is desired, then the voltage on row line 105, 113 having a memory element

which is written to a low resistance state, may be at a voltage level near V_{cc} during operation of the sense amplifier 210, which will automatically rewrite (refresh) the read cell to the low resistance state.

[00030] Because programmable contact memory elements are resistive rather than capacitive memory elements, it is possible they will take longer to pull the digit lines up to V_{cc} and to ground than a typical capacitive memory element found within a DRAM. Supposing that to be true, older DRAM sense amplifier designs that run somewhat slower than the latest generation of DRAM sense amplifiers could also be used with PCRAM memory cells. The advantage of doing so would be that these older DRAM sense amplifiers have already been shown to perform effectively, and their test infrastructure is already confirmed. Consequently, a hybrid memory consisting of PCRAM memory elements using DRAM sense amplifiers can be produced having the advantages of PCRAM technology, yet being producible quickly and inexpensively.

[00031] Although Figure 2 shows the complementary programmable contact memory element 102 and 106 and associated access transistors and digit lines D and D* as being provided in the same memory array, the complementary memory elements, access transistors and digit lines may also be provided in respective different memory arrays.

[00032] Figure 6 is a block diagram of a processor-based system 400 utilizing a PCRAM memory device 200 constructed in accordance with one of the embodiments of the present invention. The processor-based system 400 may be a computer system, a process control system or any other system employing a processor and associated memory. The system 400 includes a central processing

unit (CPU) 402, e.g., a microprocessor, that communicates with the PCRAM memory device 408 and an I/O device 404 over a bus 420. It must be noted that the bus 420 may be a series of buses and bridges commonly used in a processor-based system, but for convenience purposes only, the bus 420 has been illustrated as a single bus. A second I/O device 406 is illustrated, but is not necessary to practice the invention. The processor-based system 400 also includes read-only memory (ROM) 410 and may include peripheral devices such as a floppy disk drive 412 and a compact disk (CD) ROM drive 414 that also communicates with the CPU 402 over the bus 420 as is well known in the art.

[00033] One or more memory devices 200 may be provided on a plug-in memory module 256, e.g. SIMM, DIMM or other plug-in memory module, for easy connection with or disconnection from the bus 420. While the invention has been described and illustrated with reference to specific exemplary embodiments, it should be understood that many modifications and substitutions can be made without departing from the spirit and scope of the invention. Accordingly, the invention is not to be considered as limited by the foregoing description but is only limited by the scope of the appended claims.